## NSN 5306-00-207-5064



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-207-5064 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.370 inches **Fastener Length:** Between 3.535 inches and 3.565 inches **Head Style:** Hexagon **Head Height:** Between 0.210 inches and 0.259 inches Width Between Flats: 0.562 inches **Shank Unthreaded Hole Diameter:** 0.104 inches and 0.109 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** Between 3.165 inches and 3.195 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 3.380 inches and 3.395 inches first hole **Product Name:** Navy special project Material: Steel comp 8630 **Material Specification:** Mil-s-6050 military specification single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf

N/a
Unit Of Measure:

Shelf Life:

## NSN 5306-00-207-5064

Machine Bolt - Page 2 of 2



_		 				
וו	em	1+2	riz	211	n	٠-

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.