NSN 5306-00-207-5167

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-207-5167 **Thread Direction:** Right-hand Thread Length: Between 0.615 inches and 0.690 inches Fastener Length: Between 0.740 inches and 0.760 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.272 inches and 0.292 inches Width Between Flats: Between 0.300 inches and 0.315 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.080 inches First Diameter From Head: Between 0.218 inches and 0.228 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.065 inches and 0.125 inches **Thread Diameter:** 0.250 inches **Nonstandard Thread Pitch Diameter:** +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Ams 5616 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Deminanzat

No

NSN 5306-00-207-5167 Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0