NSN 5306-00-207-5172

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-207-5172 **Thread Direction:** Right-hand **Thread Length:** Between 0.512 inches and 0.542 inches Fastener Length: Between 0.740 inches and 0.760 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.272 inches and 0.292 inches Width Between Flats: Between 0.300 inches and 0.315 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.080 inches First Diameter From Head: Between 0.218 inches and 0.228 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.065 inches and 0.125 inches **Thread Diameter:** 0.250 inches **Nonstandard Thread Pitch Diameter:** +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 601 **Material Specification:** Ams 6304 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unf

Shelf Life: N/a

NSN 5306-00-207-5172

Externally Relieved Body Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0