

View Online at <https://aerobasegroup.com/nsn/5306-00-207-5187>

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

Between 0.490 inches and 0.510 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.365 inches and 0.385 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.070 inches and 0.080 inches

Hole Diameter:

0.065 inches

First Diameter From Head:

Between 0.247 inches and 0.251 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.125 inches

Thread Diameter:

0.312 inches

Hole Quantity:

2

Hole Type:

Drilled

Nonstandard Thread Pitch Diameter:

+0.2800/+0.2824 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Externally Relieved Body Diameter Quantity:

1

Material:

Stainless steel

Material Specification:

Ams 5616 assn standard single material response

Precious Material:

Silver

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0