

View Online at <https://aerobasegroup.com/nsn/5306-00-207-5190>

**Thread Direction:**

Right-hand

**Thread Length:**

0.438 inches

**Fastener Length:**

Between 0.552 inches and 0.572 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.365 inches and 0.385 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.490 inches and 0.510 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**Hole Diameter:**

0.065 inches

**First Diameter From Head:**

Between 0.251 inches and 0.274 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.125 inches

**Thread Diameter:**

0.312 inches

**Hole Quantity:**

2

**Hole Type:**

Drilled

**Nonstandard Thread Pitch Diameter:**

+0.2800/+0.2824 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Stainless steel

**Material Specification:**

Ams 5616 assn standard single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0