NSN 5306-00-207-5190

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-207-5190 **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 0.552 inches and 0.572 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **Hole Diameter:** 0.065 inches **First Diameter From Head:** Between 0.251 inches and 0.274 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches **Thread Diameter:** 0.312 inches **Hole Quantity:** 2 **Hole Type:** Drilled **Nonstandard Thread Pitch Diameter:** +0.2800/+0.2824 inches Thready Qty Per Inch (tpi): Hardness Rating: 30.0 rockwell c and 38.0 rockwell c **Hole Configuration Style:** Double hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel

Material Specification:

Ams 5616 assn standard single material response

NSN 5306-00-207-5190

Externally Relieved Body Bolt - Page 2 of 2



Precious Material:
Silver
Surface Treatment:
Silver
Surface Treatment Specification:
Ams 2410 assn standard single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0