NSN 5306-00-207-5908



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-207-5908 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.690 inches **Fastener Length:** 2.130 inches **Head Style:** Hexagon **Head Height:** 0.330 inches Width Between Flats: 0.625 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.111 inches first hole **Thread Diameter:** 0.438 inches **Grip Length:** 1.440 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 36.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 2.020 inches first hole Material: Steel comp 4340 or steel comp 9840 or steel comp 4640 **Material Specification:** Qq-s-624 federal specification all material responses **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-c-16232 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5306-00-207-5908

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-16232 spec.