NSN 5306-00-207-6882

Externally Relieved Body Bolt - Page 1 of 2



<u> </u>
View Online at https://aerobasegroup.com/nsn/5306-00-207-6882
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.678 inches and 0.758 inches
Fastener Length:
Between 1.240 inches and 1.260 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.334 inches and 0.354 inches
Width Between Flats:
Between 0.362 inches and 0.377 inches
Extended Washer Diameter:
Between 0.490 inches and 0.510 inches
Extended Washer Thickness:
Between 0.070 inches and 0.090 inches
First Diameter From Head:
Between 0.276 inches and 0.286 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.502 inches and 0.562 inches
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 8740
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams 2400 assn standard single treatment response
Thread Series Designator:
Unc
Shelf Life:

N/a

NSN 5306-00-207-6882

Externally Relieved Body Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0