

View Online at <https://aerobasegroup.com/nsn/5306-00-207-6882>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.678 inches and 0.758 inches

**Fastener Length:**

Between 1.240 inches and 1.260 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.334 inches and 0.354 inches

**Width Between Flats:**

Between 0.362 inches and 0.377 inches

**Extended Washer Diameter:**

Between 0.490 inches and 0.510 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.090 inches

**First Diameter From Head:**

Between 0.276 inches and 0.286 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.502 inches and 0.562 inches

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 8740

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0