NSN 5306-00-207-7696



Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter:	View Onlir	ne at https://aerobasegroup.com/nsn/5306-00-207-7696
Thread Direction: Right-hand Thread Length: 0.656 inches Fastener Length: 1.344 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.188 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Thread C	ass:
Right-hand Right-hand Thread Length: 0.656 inches Fastener Length: 1.344 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.188 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	3a	
Thread Length: 0.656 inches Fastener Length: 1.344 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.188 inches Shank Unthreaded Hole Diameter: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Sheff Life: N/a Unit Of Measure: 	Thread Di	rection:
0.656 inches Fastener Length: 1.344 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.188 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Sheff Life: N/a Unit Of Measure: 	Right-hand	b
Fastener Length: 1.344 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Thread Le	ength:
1.344 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	0.656 inch	es
Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Fastener	Length:
Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	1.344 inch	es
Head Height: 0.188 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Head Styl	e:
0.188 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	Hexagon	
Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cent 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Head Heig	ght:
0.500 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	0.188 inch	es
Shank Unthreaded Hole Diameter: 0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Width Bet	ween Flats:
0.076 inches first hole Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	0.500 inch	es
Thread Diameter: 0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Shank Un	threaded Hole Diameter:
0.312 inches Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	0.076 inch	es first hole
Grip Length: 0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: -	Thread Di	ameter:
0.688 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	0.312 inch	es
Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Grip Leng	yth:
Finished head Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	0.688 inch	es
Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Features	Provided:
24 Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	Finished h	ead
Distance From Head Largest Bearing Surface To Shank Hole Cen 1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	Thready C	Qty Per Inch (tpi):
1.172 inches first hole Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	24	
Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	Distance	From Head Largest Bearing Surface To Shank Hole Cente
Steel comp 321 Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	1.172 inch	es first hole
Material Specification: Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	Material:	
Ams 5645 assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	Steel com	p 321
Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:	Material S	specification:
Unf Shelf Life: N/a Unit Of Measure:	Ams 5645	assn standard single material response
Shelf Life: N/a Unit Of Measure:	Thread Se	eries Designator:
N/a Unit Of Measure:	Unf	
Unit Of Measure:	Shelf Life	:
	N/a	
 Demilitarization:	Unit Of M	easure:
Demilitarization:		
	Demilitari	zation:
No	No	
Fiig:	Fiig:	