## NSN 5306-00-208-0201

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-208-0201



#### Thread Class: 3a

Thread Direction:

Right-hand

#### Thread Length:

Between 0.803 inches and 0.813 inches

#### Fastener Length:

Between 1.948 inches and 1.978 inches

#### Head Style:

Double hexagon w/hole

#### **Head Height:**

0.435 inches

Width Between Flats:

Between 0.494 inches and 0.503 inches

#### **Extended Washer Diameter:**

Between 0.740 inches and 0.750 inches

#### **Extended Washer Thickness:**

Between 0.078 inches and 0.088 inches

#### **Thread Diameter:**

0.438 inches

Grip Length:

Between 1.145 inches and 1.165 inches

### Features Provided:

Finished head

#### Thready Qty Per Inch (tpi):

20

#### Min. Tensile Strength (psi):

180000 pounds per square inch

#### Hardness Rating:

40.0 rockwell c and 43.0 rockwell c

#### Material:

Steel comp e4340 or steel comp 8740

#### Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

#### Thread Series Designator:

Unf

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-00-208-0201

Machine Bolt - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

