

View Online at <https://aerobasegroup.com/nsn/5306-00-208-0261>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.365 inches and 0.395 inches

Fastener Length:

8.780 inches

Head Style:

Round w/wrench flats

Head Diameter:

3.000 inches

Head Height:

0.250 inches

Width Between Flats:

Between 2.478 inches and 2.488 inches

Concentric Hole Diameter:

1.375 inches

Thread Diameter:

2.000 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

150000 pounds per square inch

Special Features:

1slot in thread end 0.250 in. Wide by 0.500 in. Deep and undercut between head and grip 1.975 in. Min 1.985 in. Maximum diameter by 0.170 in. Wide and undercut between grip and threads 1.896 in. Min 1.906 in. Maximum diameter by 0.190 in. Min 0.220 in. Maximum wide

Material:

Steel comp 8630

Material Specification:

Mil-s-6050 military specification single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

type 2.Fscm 98897 mfr ref single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.