

View Online at <https://aerobasegroup.com/nsn/5306-00-208-0286>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.626 inches

**Fastener Length:**

4.694 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

1.438 inches

**Head Height:**

0.125 inches

**Width Between Flats:**

1.250 inches

**Shoulder Diameter:**

0.998 inches

**Shoulder Length:**

3.938 inches

**Shank Unthreaded Hole Diameter:**

0.190 inches first hole

**Counterbore Diameter:**

0.562 inches

**Counterbore Depth:**

3.930 inches

**Concentric Hole Diameter:**

0.500 inches

**Thread Diameter:**

0.875 inches

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

200000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.500 inches first hole

**Material:**

Steel comp e4340

**Material Specification:**

Mil-s-5000, cond c military specification single material response

**Surface Treatment:**

Cadmium head

**Style Designator:**

Counterbore unthreaded

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.