

View Online at <https://aerobasegroup.com/nsn/5306-00-208-0286>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.626 inches

Fastener Length:

4.694 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.438 inches

Head Height:

0.125 inches

Width Between Flats:

1.250 inches

Shoulder Diameter:

0.998 inches

Shoulder Length:

3.938 inches

Shank Unthreaded Hole Diameter:

0.190 inches first hole

Counterbore Diameter:

0.562 inches

Counterbore Depth:

3.930 inches

Concentric Hole Diameter:

0.500 inches

Thread Diameter:

0.875 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

200000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.500 inches first hole

Material:

Steel comp e4340

Material Specification:

Mil-s-5000, cond c military specification single material response

Surface Treatment:

Cadmium head

Style Designator:

Counterbore unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.