

View Online at <https://aerobasegroup.com/nsn/5306-00-208-0665>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.530 inches and 0.590 inches

**Fastener Length:**

3.080 inches

**Head Style:**

Hexagon

**Head Height:**

0.250 inches

**Width Between Flats:**

Between 1.615 inches and 1.628 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.166 inches first hole

**Concentric Hole Diameter:**

0.560 inches

**Thread Diameter:**

1.125 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.900 inches first hole

**Material:**

Steel

**Material Specification:**

Mil-s-6758 military specification single material response or mil-s-6050 military specification single material response or mil-s-5626 military specification single material response

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.