Externally Relieved Body Bolt - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5306-00-208-0840

View C	Online at https://aerobasegroup.com/nsn/5306-00-208-0840
Thread	d Class:
3a	
Thread	d Direction:
Right-ł	nand
Thread	d Length:
Betwee	en 0.760 inches and 0.820 inches
Faster	ner Length:
3.800 i	nches
Head S	Style:
Hexag	on
Head I	Height:
0.344 i	nches
Width	Between Flats:
Betwee	en 0.741 inches and 0.750 inches
Hole D	Diameter:
0.070 i	nches
First D	Diameter From Head:
Betwee	en 0.494 inches and 0.500 inches
Secon	d Diameter From Head:
Betwee	en 0.387 inches and 0.391 inches
Distan	ce From Largest Bearing Surface Of Head To End Of First Diameter:
Betwee	en 0.480 inches and 0.520 inches
Distan	ce From Largest Bearing Surface Of Head To End Of Second Diameter:
Betwee	en 3.718 inches and 3.724 inches
Thread	d Diameter:
0.500 i	nches
Hole C	Quantity:
6	
Hole T	уре:
Drilled	
Thread	dy Qty Per Inch (tpi):
20	
Hardn	ess Rating:
26.0 rc	ockwell c and 32.0 rockwell c
Hole C	Configuration Style:
Hexag	on flats
Extern	ally Relieved Body Diameter Quantity:
2	
Materi	al:
Steel	
Thread	d Series Designator:
	-

Unf

NSN 5306-00-208-0840

Externally Relieved Body Bolt - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0