## NSN 5306-00-208-3936

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-208-3936
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.825 inches
Fastener Length:
5.140 inches
Head Style:
Hexagon
Head Height:
0.500 inches
Width Between Flats:
1.500 inches
Shoulder Diameter:
Between 0.999 inches and 1.000 inches
Shoulder Length:
Between 4.312 inches and 4.317 inches
Shank Unthreaded Hole Diameter:
0.140 inches first hole and 0.144 inches first hole
Concentric Hole Diameter:
Between 0.467 inches and 0.473 inches
Thread Diameter:
0.875 inches
Thready Qty Per Inch (tpi):
14
Hardness Rating:
34.0 rockwell c and 39.0 rockwell c
Distance From Head Largest Bearing Surface To Shank Hole Center:
4.977 inches first hole
Material:
Steel comp 4340
Material Specification:
Sae assn standard single material response
Surface Treatment:
Cadmium
Style Designator:
Concentric hole unthreaded
Thread Series Designator:
Unf
Shelf Life:

N/a

## NSN 5306-00-208-3936

Internally Relieved Body Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0