## NSN 5306-00-208-6090

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-208-6090

3a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

0.641 inches

#### Fastener Length:

3.453 inches

**Head Style:** 

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

#### Width Between Flats:

Between 0.553 inches and 0.565 inches

#### Thread Diameter:

0.375 inches

#### Grip Length:

2.812 inches

#### **Features Provided:**

Finished head

Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

125000 pounds per square inch

#### Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

#### Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

#### Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8695 military specification 6th material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

#### **Thread Series Designator:**

Unf

Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

# NSN 5306-00-208-6090

Machine Bolt - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-s-5626 spec.

