

View Online at <https://aerobasegroup.com/nsn/5306-00-208-6389>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.600 inches

Fastener Length:

3.240 inches

Head Style:

Hexagon

Head Height:

0.420 inches

Width Between Flats:

1.625 inches

Shoulder Diameter:

1.057 inches first shoulder and 1.060 inches first shoulder

Shoulder Length:

0.640 inches first shoulder

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.060 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.