NSN 5306-00-208-7652



Externally Relieved Body Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-208-7652 **Thread Direction:** Right-hand **Thread Length:** Between 0.460 inches and 0.480 inches Fastener Length: Between 1.770 inches and 1.790 inches **Head Style:** Hexagon **Head Height:** Between 0.193 inches and 0.213 inches Width Between Flats: 0.500 inches **Hole Diameter:** 0.062 inches **First Diameter From Head:** Between 0.309 inches and 0.312 inches **Second Diameter From Head:** Between 0.229 inches and 0.233 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.115 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.175 inches and 1.195 inches **Thread Diameter:** 0.312 inches **Nonstandard Thread Pitch Diameter:** +0.2800/+0.2824 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 30.0 rockwell c and 38.0 rockwell c **Hole Configuration Style:** Hexagon flats **Externally Relieved Body Diameter Quantity:** 2 Material: Steel **Material Specification:**

Pwa722, fscm 77445 mfr ref single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Pwa43, fscm 77445 mfr ref single treatment response

NSN 5306-00-208-7652

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0