

View Online at <https://aerobasegroup.com/nsn/5306-00-208-7653>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.420 inches and 0.460 inches

Fastener Length:

2.000 inches

Head Style:

Hexagon extended washer

Head Height:

0.328 inches

Width Between Flats:

0.500 inches

Extended Washer Diameter:

0.780 inches

Extended Washer Thickness:

0.090 inches

Hole Diameter:

0.063 inches

First Diameter From Head:

Between 0.432 inches and 0.438 inches

Second Diameter From Head:

Between 0.366 inches and 0.370 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.100 inches and 0.140 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.540 inches and 1.580 inches

Thread Diameter:

0.438 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Hardness Rating:

32.0 rockwell c and 36.0 rockwell c

Hole Configuration Style:

Hexagon flats

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp 8735

Material Specification:

Ams 6320 assn standard single material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0