## NSN 5306-00-208-7661

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-208-7661 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.550 inches and 0.590 inches **Fastener Length:** 3.030 inches **Head Style:** Dee chamfer **Head Diameter:** 0.770 inches **Head Height:** Between 0.120 inches and 0.135 inches **Distance From Centerline To Flat:** Between 0.338 inches and 0.342 inches First Diameter From Head: Between 0.366 inches and 0.368 inches **Second Diameter From Head:** Between 0.285 inches and 0.289 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.140 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 2.440 inches and 2.480 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c Minimum Yield Strength: 100000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 8740 or steel comp 4140 **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5306-00-208-7661

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0