

View Online at <https://aerobasegroup.com/nsn/5306-00-211-8397>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.357 inches and 1.407 inches

**Fastener Length:**

Between 1.867 inches and 1.897 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.918 inches and 0.938 inches

**Width Between Flats:**

Between 1.052 inches and 1.064 inches

**Extended Washer Diameter:**

Between 1.615 inches and 1.625 inches

**Extended Washer Thickness:**

Between 0.212 inches and 0.232 inches

**Grip Diameter:**

Between 0.9980 inches and 0.9990 inches

**Thread Diameter:**

1.000 inches

**Grip Length:**

Between 1.490 inches and 1.510 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.