

View Online at <https://aerobasegroup.com/nsn/5306-00-211-8481>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.547 inches and 0.597 inches

**Fastener Length:**

Between 2.932 inches and 2.962 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.375 inches and 0.390 inches

**Width Between Flats:**

Between 1.052 inches and 1.064 inches

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 2.365 inches and 2.385 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.794 inches first hole and 2.844 inches first hole

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1112 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.