

View Online at <https://aerobasegroup.com/nsn/5306-00-214-5469>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

4.875 inches

Head Style:

Hexagon

Head Height:

0.188 inches

Width Between Flats:

0.937 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

First Diameter From Head:

Between 0.593 inches and 0.613 inches

Second Diameter From Head:

Between 0.623 inches and 0.624 inches

Third Diameter From Head:

Between 0.593 inches and 0.613 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.063 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

4.437 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

4.500 inches

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

150000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.750 inches first hole

Externally Relieved Body Diameter Quantity:

3

Material:

Steel comp 4130

Material Specification:

Sae assn standard single material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0