

View Online at <https://aerobasegroup.com/nsn/5306-00-221-1320>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.687 inches and 0.727 inches

**Fastener Length:**

Between 4.322 inches and 4.342 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.395 inches and 0.415 inches

**Width Between Flats:**

0.497 inches

**Extended Washer Diameter:**

0.645 inches

**Extended Washer Thickness:**

Between 0.065 inches and 0.085 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 3.615 inches and 3.635 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

50.0 rockwell c and 56.0 rockwell c

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Wk-151267 type 2 fscm 33525 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0