## NSN 5306-00-223-1485

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-223-1485

## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.630 inches and 0.690 inches

#### Fastener Length:

1.000 inches

#### Head Style:

Double hexagon w/hole

#### **Head Height:**

0.260 inches

## Width Between Flats:

Between 0.243 inches and 0.251 inches

## **Extended Washer Diameter:**

0.375 inches

## **Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

## **Thread Diameter:**

0.190 inches

## Grip Length:

Between 0.310 inches and 0.370 inches

## Features Provided:

Finished head

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

195000 pounds per square inch

## Hardness Rating:

42.0 rockwell c and 46.0 rockwell c

## Surface Finish:

32.0 microinches threads

## Material:

Steel comp 601

## **Material Specification:**

Ams 6304 assn standard single material response

## Surface Treatment:

Nickel and cadmium

## Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

## **Thread Series Designator:**

Unjf



# NSN 5306-00-223-1485

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

