NSN 5306-00-223-9948

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-223-9948 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.325 inches and 0.330 inches **Fastener Length:** 1.410 inches **Head Style:** Dee **Head Diameter:** Between 0.800 inches and 0.840 inches **Head Height:** Between 0.115 inches and 0.125 inches **Distance From Centerline To Flat:** Between 0.320 inches and 0.325 inches **Shoulder Diameter:** 0.410 inches first shoulder and 0.412 inches first shoulder **Shoulder Length:** 1.005 inches first shoulder and 1.010 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.075 inches first hole and 0.078 inches first hole **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 46.0 rockwell c and 48.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 1.250 inches first hole **Shoulder Shape:** Round first shoulder **Special Features:** Color white Material: Steel **Surface Treatment:** Cadmium and chromium and paint **Thread Series Designator:**

Unf

Shelf Life:

N/a

NSN 5306-00-223-9948

Shoulder Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0