

View Online at <https://aerobasegroup.com/nsn/5306-00-224-0927>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.450 inches

**Fastener Length:**

1.780 inches

**Head Style:**

Hexagon

**Head Height:**

0.150 inches

**Width Between Flats:**

0.750 inches

**Shoulder Diameter:**

0.4989 inches first shoulder and 0.4994 inches first shoulder

**Shoulder Length:**

1.330 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.126 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.620 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5002 spec.