## NSN 5306-00-224-9268

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-224-9268

Thre	ead Class:
3a	
Thre	ead Direction:
Righ	nt-hand
-	ead Length:
	veen 0.236 inches and 0.246 inches
Fast	tener Length:
	0 inches
Неа	d Diameter:
Betv	veen 0.262 inches and 0.270 inches
Неа	d Height:
	veen 0.159 inches and 0.164 inches
Firs	t Diameter From Head:
Betv	veen 0.125 inches and 0.130 inches
Dist	ance From Largest Bearing Surface Of Head To End Of First Diameter:
	veen 0.344 inches and 0.354 inches
Inte	rnal Drive Style:
	agon
Thre	ead Diameter:
0.16	64 inches
Wid	th Across Flats:
Betv	veen 0.140 inches and 0.142 inches
Thre	eady Qty Per Inch (tpi):
32	
Pro	duct Name:
Nav	y special project
Mat	erial:
Stee	el comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Mat	erial Specification:
66 fe	ederal standard all material responses
Sur	face Treatment:
Pas	sivate
Sur	face Treatment Specification:
Qq-I	p-35 federal specification single treatment response
Thre	ead Series Designator:
Unc	
She	If Life:
N/a	
Unit	t Of Measure:
 Den	nilitarization:
No	

## NSN 5306-00-224-9268

Internal Wrenching Bolt - Page 2 of 2

Fiig: A003b0

