NSN 5306-00-224-9332



Internal Wrenching Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-224-9332 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.211 inches and 0.303 inches **Fastener Length:** Between 0.359 inches and 0.391 inches **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** 0.047 inches **First Diameter From Head:** Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.088 inches and 0.148 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches **Hole Quantity:** 6 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi):

125000 pounds per square inch

Minimum Yield Strength:

80000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Surface Finish:

63.0 microinches grip

Material:

Steel comp 304

Material Specification:

Qq-s-763 federal specification single material response

NSN 5306-00-224-9332

Internal Wrenching Bolt - Page 2 of 2



Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0