NSN 5306-00-225-1578

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-225-1578

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.635 inches and 0.655 inches
Fastener Length:
2.270 inches
Head Style:
Double hexagon w/hole
Head Height:
0.388 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
0.091 inches
Hole Diameter:
0.055 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Round
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140
Surface Treatment:

Cadmium and chromate

NSN 5306-00-225-1578

Shear Bolt - Page 2 of 2



Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0