

View Online at <https://aerobasegroup.com/nsn/5306-00-225-5822>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.600 inches

Fastener Length:

2.650 inches

Head Diameter:

1.200 inches

Head Height:

0.250 inches

Distance From Centerline To Flat:

0.475 inches

Shank Unthreaded Hole Diameter:

0.143 inches first hole and 0.149 inches first hole

Concentric Hole Diameter:

0.375 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.450 inches first hole

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.