NSN 5306-00-225-6708

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-225-6708 **Thread Class:** 1a **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 3.125 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.330 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** 0.500 inches **Extended Washer Thickness:** Between 0.057 inches and 0.063 inches **First Diameter From Head:** Between 0.218 inches and 0.228 inches **Second Diameter From Head:** Between 0.240 inches and 0.247 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.375 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.125 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Minimum Yield Strength: 85000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 2 Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response **Surface Treatment: Passivate**

Thread Series Designator: Unf

NSN 5306-00-225-6708

Externally Relieved Body Bolt - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0