NSN 5306-00-225-9090

Machine Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-00-225-9090 |
|-----------------------------------------------------------------------------------------------------------------------------------|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.875 inches and 1.062 inches |
| Fastener Length: |
| Between 1.094 inches and 1.125 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.195 inches and 0.211 inches |
| Width Between Flats: |
| Between 0.489 inches and 0.500 inches |
| Thread Diameter: |
| 0.312 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 120000 pounds per square inch |
| Hardness Rating: |
| 25.0 rockwell c and 34.0 rockwell c |
| Material: |
| Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 |
| or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp |
| 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel |
| comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541 |
| Material Specification: |
| Sae j429 assn standard all material responses |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Specification Or Standard: |
| 2 type and 10p style and 5 grade |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NI

Demilitarization:

NSN 5306-00-225-9090 Machine Bolt - Page 2 of 2



Fiig:

A003b0