NSN 5306-00-226-4826

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-226-4826 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.705 inches and 0.875 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Hexagon **Head Height:** Between 0.195 inches and 0.211 inches Width Between Flats: Between 0.489 inches and 0.500 inches **End Application:** Mrap rg-33; mrap - m-atv with cs13 pop and sne **Thread Diameter:** 0.312 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 150000 pounds per square inch **Surface Finish:** 63.0 microinches threads Material: Steel **Material Specification:** Sae j429 grade 8 assn standard single material response or astm a354 grade bd assn standard single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633 type 2 sc 3 assn standard single treatment response **Thread Series Designator:** Unc **Specification Data:** 05047-aeb02c313875aw9a91 professional/industrial association specification

N/a

Shelf Life:

Unit Of Measure:

NSN 5306-00-226-4826

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0