
# NSN 5306-00-226-4827

Machine Bolt - Page 1 of 2





# **Thread Class:**

2a

**Thread Direction:** 

**Right-hand** 

# **Thread Length:**

Between 0.830 inches and 1.000 inches

#### Fastener Length:

Between 0.969 inches and 1.000 inches

#### Head Style:

Hexagon

Head Height:

Between 0.195 inches and 0.211 inches

#### Width Between Flats:

Between 0.489 inches and 0.500 inches

#### End Application:

Mrap rg-33; mrap - matv with cs13 pop and sne; mrap buffalo mk2a2; mrap - cougar cat1 a1

#### Thread Diameter:

0.312 inches

## **Features Provided:**

Finished head

# Thready Qty Per Inch (tpi):

18

# Min. Tensile Strength (psi):

150000 pounds per square inch

## Surface Finish:

63.0 microinches threads

#### Material:

Steel

#### **Material Specification:**

Sae j429 grade 8 assn standard single material response or astm a354 grade bd assn standard single material response

#### Surface Treatment:

Zinc

# Surface Treatment Specification:

Astm b633 assn standard single treatment response

# **Thread Series Designator:**

Unc

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# **NSN 5306-00-226-4827** Machine Bolt - Page 2 of 2

Fiig: A003b0

