

View Online at <https://aerobasegroup.com/nsn/5306-00-226-4828>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.875 inches and 1.063 inches

**Fastener Length:**

Between 1.063 inches and 1.125 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.195 inches and 0.211 inches

**Width Between Flats:**

Between 0.489 inches and 0.500 inches

**End Application:**

Mrap rg-33; mrap - matv with cs13 pop

**Thread Diameter:**

0.312 inches

**Grip Length:**

0.250 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel

**Material Specification:**

Sae j429 grade 8 assn standard single material response or astm a354 grade bd assn standard single material response

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astm b633 type 2 sc 3 assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0