

View Online at <https://aerobasegroup.com/nsn/5306-00-226-4985>

**Thread Direction:**

Right-hand

**Thread Length:**

0.850 inches

**Fastener Length:**

Between 0.928 inches and 0.948 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Hole Diameter:**

0.062 inches

**Shank Unthreaded Hole Diameter:**

0.060 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

0.098 inches

**Hole Type:**

Drilled

**Features Provided:**

Unfinished head

**Nonstandard Thread Pitch Diameter:**

+0.2213/+0.2238 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.820 inches first hole and 0.840 inches first hole

**Material:**

Steel comp 601

**Material Specification:**

Ams 6304 assn standard single material response

**Surface Treatment:**

Nickel and cadmium

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0