

View Online at <https://aerobasegroup.com/nsn/5306-00-226-4985>

Thread Direction:

Right-hand

Thread Length:

0.850 inches

Fastener Length:

Between 0.928 inches and 0.948 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Hole Diameter:

0.062 inches

Shank Unthreaded Hole Diameter:

0.060 inches first hole and 0.080 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

0.098 inches

Hole Type:

Drilled

Features Provided:

Unfinished head

Nonstandard Thread Pitch Diameter:

+0.2213/+0.2238 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.820 inches first hole and 0.840 inches first hole

Material:

Steel comp 601

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Nickel and cadmium

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0