## NSN 5306-00-228-2891



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-228-2891 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.609 inches and 0.688 inches **Fastener Length:** Between 0.687 inches and 0.734 inches **Head Style:** Hexagon **Head Height:** Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.046 inches and 0.078 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 62000 pounds per square inch Material: Aluminum alloy **Material Specification:** Qq-a-200 federal specification single material response or qq-a-225 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Oxide film and anodize **Surface Treatment Specification:** Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life:

--**Demilitarization:**No **Fiig:** 

**Unit Of Measure:** 

A003b0

N/a

## NSN 5306-00-228-2891

Machine Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-c-5541 spec.