NSN 5306-00-229-3609

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-229-3609

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.750 inches and 0.810 inches
Fastener Length:
1.875 inches
Head Style:
Hexagon
Head Height:
0.250 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 1.065 inches and 1.125 inches
Hole Quantity:
6
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
248.0 brinell standard and 341.0 brinell standard
248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength:
Minimum Yield Strength:
Minimum Yield Strength: 85000 pounds per square inch
Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style:
Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon longitudinal hole
Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon longitudinal hole Surface Finish:
Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 32.0 microinches threads
Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material:

NSN 5306-00-229-3609

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A003b0