Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-231-0516

Inread	d Class:
2a	
Thread	d Direction:
Right-h	nand
Thread	d Length:
0.313 i	nches
Fasten	ner Length:
0.875 i	nches
Head S	Style:
Hexago	on
Head H	Height:
Betwee	en 0.109 inches and 0.141 inches
Width	Between Flats:
Betwee	en 0.365 inches and 0.377 inches
First D	Diameter From Head:
Betwee	en 0.136 inches and 0.140 inches
Distan	ce From Largest Bearing Surface Of Head To End Of First Diameter:
0.562 i	nches
Threac	d Diameter:
0.190 i	nches
Threac	dy Qty Per Inch (tpi):
32	
Extern	ally Relieved Body Diameter Quantity:
1	
Materia	al:
Steel c	comp 304 or steel comp 316
Materia	al Specification:
Qq-s-7	63 federal specification all material responses
Surfac	e Treatment:
Passiva	ate or oxide
Surfac	e Treatment Specification:
Qq-p-3	5 federal specification 1st treatment response or mil-c-13924, class 3 military specification 2nd treatment response
Threac	d Series Designator:
Unf	
Shelf L	Life:
N/a	
Unit O	f Measure:
Demili	tarization:
No	
Fiig:	
A003b0	0

Externally Relieved Body Bolt - Page 2 of 2

Mil-std (military Standard):

Mil-c-13924 spec.

