## NSN 5306-00-235-0603

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-235-0603

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.374 inches and 0.453 inches
Fastener Length:
Between 6.015 inches and 6.062 inches
Head Style:
Hexagon
Head Height:
Between 0.109 inches and 0.141 inches
Width Between Flats:
Between 0.365 inches and 0.377 inches
Hole Diameter:
0.046 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 5.609 inches and 5.641 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c
-
26.0 rockwell c and 32.0 rockwell c
26.0 rockwell c and 32.0 rockwell c  Hole Configuration Style:
26.0 rockwell c and 32.0 rockwell c  Hole Configuration Style:  Hexagon flats
26.0 rockwell c and 32.0 rockwell c  Hole Configuration Style:  Hexagon flats  Material:
26.0 rockwell c and 32.0 rockwell c  Hole Configuration Style:  Hexagon flats  Material:  Steel comp 431
26.0 rockwell c and 32.0 rockwell c  Hole Configuration Style: Hexagon flats  Material: Steel comp 431  Material Specification:
26.0 rockwell c and 32.0 rockwell c  Hole Configuration Style:  Hexagon flats  Material:  Steel comp 431  Material Specification:  Mil-s-18732 military specification single material response

Unf

## NSN 5306-00-235-0603

Machine Bolt - Page 2 of 2



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.