

View Online at <https://aerobasegroup.com/nsn/5306-00-237-6723>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.439 inches and 0.514 inches

**Fastener Length:**

Between 0.516 inches and 0.561 inches

**Head Style:**

Undercut hexagon

**Head Height:**

0.180 inches

**Width Between Flats:**

Between 0.490 inches and 0.502 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.047 inches and 0.077 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Special Features:**

Furnished with one silicone o-ring and one polytetrafluoroethylene washer

**Material:**

Steel

**Surface Treatment:**

Passivate

**Special Test Features:**

Special quality control testing

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Reference Number Differentiating Characteristics:**

As differentiated by packaging which must conform to ships parts control center special quality control provisions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0