## NSN 5306-00-238-1068



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-238-1068 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.615 inches and 0.695 inches **Fastener Length:** Between 1.740 inches and 1.760 inches **Head Style:** Hexagon **Head Height:** Between 0.178 inches and 0.198 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Shank Unthreaded Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.065 inches and 1.125 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): C8 Hardness Rating: 35.0 rockwell c and 40.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 1.600 inches first hole and 1.620 inches first hole **Surface Finish:** 32.0 microinches threads Material: Steel **Material Specification:** Ams 5613 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf

Unji

Shelf Life:

N/a

## **NSN 5306-00-238-1068** Machine Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A003b0