

View Online at <https://aerobasegroup.com/nsn/5306-00-238-1068>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.615 inches and 0.695 inches

**Fastener Length:**

Between 1.740 inches and 1.760 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.178 inches and 0.198 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Shank Unthreaded Hole Diameter:**

0.065 inches first hole and 0.072 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.065 inches and 1.125 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

C8

**Hardness Rating:**

35.0 rockwell c and 40.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.600 inches first hole and 1.620 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel

**Material Specification:**

Ams 5613 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0