## NSN 5306-00-240-7217

View Online at https://aerobasegroup.com/nsn/5306-00-240-7217

Shear Bolt - Page 1 of 2



**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.460 inches and 0.510 inches **Fastener Length:** Between 0.658 inches and 0.688 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.290 inches and 0.310 inches Width Between Flats: Between 0.306 inches and 0.315 inches **Extended Washer Diameter:** Between 0.430 inches and 0.440 inches **Extended Washer Thickness:** Between 0.059 inches and 0.079 inches **Hole Diameter:** 0.037 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.178 inches and 0.198 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch

**Hole Configuration Style:** 

Round

Material:

Titanium alloy

**Surface Treatment:** 

Nickel and cadmium

**Surface Treatment Specification:** 

Ams2403 assn standard 1st treatment response and qq-p-416 type 2 federal specification 2nd treatment response

## NSN 5306-00-240-7217

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0