## NSN 5306-00-242-1336



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-242-1336 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.617 inches and 0.688 inches **Fastener Length:** 0.688 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.330 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Thread Diameter:** 0.250 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-00-242-1336

Machine Bolt - Page 2 of 2



| Demi |  |  |  |
|------|--|--|--|
|      |  |  |  |
|      |  |  |  |

No

Fiig:

A003b0