## NSN 5306-00-245-0441



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-245-0441 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 1.000 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.362 inches and 0.375 inches **Hole Diameter:** 0.062 inches **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 20 **Hole Configuration Style:** Hexagon flats Material: Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 **Material Specification:** Qq-b-613 federal specification all material responses or qq-b-626 federal specification all material responses **Surface Treatment:** Silver Qq-s-365 type 2 federal specification single treatment response

Surface Treatment Specification:

Qq-s-365 type 2 federal specification single treatment of the Thread Series Designator:

Unc

Specification Or Standard:

1 type

Shelf Life:

N/a

## NSN 5306-00-245-0441

Machine Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-dtl-1222 spec.